



CAP. TONS	SPAN L	A	F	W.B.	BRIDGE WEIGHT LBS.	MAX. WHEEL LOAD LBS.	GIRDER SIZE	HP
5	20'-0"	8'-2"	1'-5"	6'-6"	2400	5200	W14x61	(2)x.55/.14 3600/900 RPM
	24'-0"	8'-2"	1'-7 1/2"	6'-6"	2800	5450	W16x67	
	28'-0"	8'-2"	1'-8"	6'-6"	3400	5700	W16x77	
	32'-0"	8'-2"	1'-8"	6'-6"	3750	5850	W16x77	
	36'-0"	8'-2"	1'-8"	6'-6"	4500	6100	W16x89	
	40'-0"	8'-2"	1'-10"	6'-6"	5250	6300	W18x97	(2)x.8/.2 3600/900 RPM
	44'-0"	8'-2"	2'-1"	6'-6"	6000	6550	W21x83 W/ C12x20.7	
	48'-0"	10'-2"	2'-1"	8'-6"	7200	6900	W21x93 W/ C12x20.7	
	52'-0"	10'-2"	2'-1"	8'-6"	8350	7200	W21x93 W/ C15x33.9	
	56'-0"	10'-2"	2'-4"	8'-6"	9000	7400	W24x94 W/ C15x33.9	
59'-0"	10'-2"	2'-7"	8'-6"	10400	7750	W27x102 W/ MC18x42.7		

	TROLLEY MODEL	
	3111D-1423	3111D-2423
LIFT	21'-0"	29'-10"
TROLLEY WEIGHT	783 LBS.	840 LBS.
DIM. E	3'-0"	3'-7"

HOISTING SPEED	16/4 FPM
BRIDGE SPEED	100/25 FPM
TROLLEY SPEED	80/20 FPM
RUNWAY RAIL	30# ASCE
POWER SUPPLY	460-3-60
WHEEL DIA.	6.3"



PRODUCT
INFORMATION

TOP RUNNING
SINGLE GIRDER CRANE

5 TON CAPACITY

DWG. NO:

17534101

DATE: 4/30/99

REVISION: 0

DWN. BY:

CHK. BY:

APP. BY: